CAMCO MFG INC -- WINDSHIELD WASHER FLUID-20, 30907 -- 7930-00N088464

Product ID:WINDSHIELD WASHER FLUID-20, 30907 MSDS Date:04/22/1997 FSC:7930 NIIN:00N088464 MSDS Number: CHPCZ === Responsible Party === Company Name: CAMCO MFG INC Address:121 LANDMARK DR City: GREENSBORO State:NC ZIP:27409 Country:US Info Phone Num: 910-668-7661 Emergency Phone Num:800-334-2004 CAGE:GO309 === Contractor Identification === Company Name: CAMCO MANUFACTURING INC Address:121 LANDMARK DR Box:City:GREENSBORO State:NC ZIP:27409 Country:US Phone:919-668-7661 CAGE:1EA43 Company Name: CAMCO MFG INC Address:121 LANDMARK DR City: GREENSBORO State:NC ZIP:27409-9603 Country:US Phone:919-668-7661 CAGE:GO309 Ingred Name:METHANOL; (METHYL ALCOHOL) (SARA 313) (CERCLA). VP:96.1 @ 20C. CAS:67-56-1 RTECS #:PC1400000 Fraction by Wt: <21% OSHA PEL:200 PPM, S ACGIH TLV:200 PPM;250 STEL, S EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ingred Name: ADDITIVES Fraction by Wt: <1% OSHA PEL:N/K ACGIH TLV:N/K Ingred Name: VOLATILE ORGANIC COMPOUNDS: COATING & MATERIAL - 1.65 LB/GAL. RTECS #:9999999VO Ingred Name:FIRE FIGHT PROC:PREVENT PRESSURE BUILD-UP & POSSIBLE

AUTO-IGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT. IF (ING 5) RTECS $\#\!:\!99999992Z$

Ingred Name:ING 4:WATER IS USED, FOG NOZZLES ARE PREFERABLE. RTECS #:99999992Z

- HDCH, SHORTNESS OF BREATH, VISUAL IMPAIRMENT & BLINDNESS. SEV POIS CAN CAUSE COMA & DEATH. INGEST OF LG AMTS OF METHYL ALCOHOL HAS BEEN SHOWN TO DMG ORGS IN CL LIVER, KIDNEY, PANCREAS, HEART, LUNGS & BRAIN. ALTHOUGH THIS RARELY OCCURS, SURVIVORS OF SEV INTOX MAY SUFFER(SUPDAT)
- Medical Cond Aggravated by Exposure:OVEREXPOSURE MAY AGGRAVATE PRE-EXISTING DISORDERS OF THE EYES.

First Aid:INHAL:REMOVE TO FRESH AIR. IF BRTHG HAS STOPPED, APPLY ARTF RESP. IF BRTHG IS DFCLT, GIVE OXYG PROVIDED QUALIFIED OPERATOR IS AVAIL. GET MED ATTN. EYES:FLUSH W/LG QTYS OF WATER FOR AT LST 15 MINS & SE EK MED ATTN. SKIN:REMOVE CONTAM CLTHG &WASH CONTAM SKIN W/LG AMTS OF SOAP & WATER. IF IRRIT PERSISTS, GET MED ATTN. LAUNDER CLTHG BEFORE REUSE. INGEST:DO NOT INDUCE VOMIT. (NEVER GIVE (SUPP DATA)

- Flash Point Method: PMCC
- Flash Point:105F,41C
- Lower Limits:7.3%
- Upper Limits:36%
- Extinguishing Media:FOAM, DRY CHEM, CARBON DIOXIDE/ANY CLASS B EXTING AGENT. WATER MAY BE UNSUITABLE AS EXTING MEDIUM, BUT HELPFUL (SUPDAT)
- Fire Fighting Procedures:USE NIOSH APPRVD SCBA & FULL PROT EQUIP . USE WATER SPRAY TO COOL FIRE EXPOS CNTNRS. WATER MAY BE INEFT, BUT MAY BE USED TO COOL EXPOS CNTNRS TO (ING 4)
- Unusual Fire/Explosion Hazard:HANDLE AS FLAMM LIQ. VAPS FORM EXPLO MIXT IN AIR BTWN UPPER & LOWER EXPLO LIMS WHICH CAN BE IGNITED BY MANY SOURCES SUCH AS PILOT LIGHTS, OPEN FLAMES, (SUPDAT)

Spill Release Procedures:KEEP SPECTATORS AWAY. ELIM ALL IGNIT SOURCES
(FLAMES, HOT SURFS & SOURCES OF ELEC, STATIC/FRICTIONAL SPKS). DIKE
& CNTN SPILL W/INERT MATL (E.G., SAND, EARTH). TRANSFER LIQS TO
COVERED METAL CNTNRS FO R RECOVERY/DISP, OR REMOVE W/INERT
ABSORBENT.

Page 3 of 3

Handling and Storage Precautions: AVOID PROLONGED OR REPEATED SKIN CONTACT. DO NOT SWALLOW. STORE IN CLOSED CONTAINERS IN A COOL, DRY, WELL VENTILATED AREA. Other Precautions: KEEP AWAY FROM SPARKS & OPEN FLAME. Respiratory Protection: USE NIOSH APPROVED RESPIRATOR WHEN TLV IS EXCEEDED. Ventilation: PROVIDE SUFFICIENT VENTILATION TO MAINTAIN EXPOSURE BELOW TLV Protective Gloves: APPROPRIATE IMPERMEABLE GLOVES. Eye Protection: ANSI APPRVD CHEM WORKERS GOGGLES . Other Protective Equipment: EYE WASH FOUNTAIN & DELUGE SHOWER WHICH MEET ANSI DESIGN CRITERIA . LONG SLEEVES & APRON IS RECOMMENDED. Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER. Supplemental Safety and Health EXTING MEDIA: IN KEEPING ADJACENT CNTNRS COOL. EXPLO HAZ: ELEC MOTORS & SWITCHES. HAZ DECOMP PROD: IN SUFFICIENT CONCS CAN ACT AS ASPHY. EFTS OF OVEREXP:PERM NEUROLOGICAL DMG. FIRST AID PROC:ANYTHING BY MOUTH TO UNCONSCIOUS PERSON). CALL POISCTL CTR, HOSPITAL EMERGENCY ROOM/MD IMMED. Boiling Pt:B.P. Text:>148F,>65C Vapor Pres:SEE ING 1 Vapor Density: HVR/AIR Spec Gravity:0.95 (H*20=1) Evaporation Rate & Reference:GREATER/N-BUTYL ACETATE Solubility in Water:SOLUBLE Appearance and Odor: CLEAR BLUE LIQUID; MILD ALCOHOL ODOR. Stability Indicator/Materials to Avoid:YES STRONG ACIDS & STRONG OXIDIZING AGENTS. Stability Condition to Avoid: IGNITION SOURCES SUCH AS HEAT, SPARKS, FLAMES. Hazardous Decomposition Products: BURNING CAN PRDCE CARBON MONOXIDE &/OR CARBON DIOXIDE. CARBON MONOXIDE IS HIGHLY TOX IF INHALED, CARBON DIOXIDE (SUPDAT) Waste Disposal Methods: DISPOSE I/A/W FEDERAL, STATE & LOCAL REGULATIONS. Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

particular situation.