

## Safety Data Sheet

Printing date 11/23/2015

Revised On 11/23/2015

**1 Identification of the substance and manufacturer**

**Trade name:** COVER UP  
**Product code:** 1436  
**Product category:** PC9a Paints and coatings.  
**Manufacturer/Supplier:** Superco Specialty Products  
 25041 Anza Drive  
 Valencia, CA 91355  
 Phone: 661-775-8877 www.supercoproducts.com  
**Emergency telephone number:** CHEMTEL 1-800-255-3924.

**2 Hazard(s) identification****Classification of the substance or mixture**

Flam. Aerosol 1 H222 Extremely flammable aerosol.  
 Press. Gas H280 Contains gas under pressure; may explode if heated.  
 Eye Irrit. 2A H319 Causes serious eye irritation.

**GHS Hazard pictograms**

GHS02 GHS04 GHS07

**Signal word**

Danger

**Hazard statements**

Extremely flammable aerosol.  
 Contains gas under pressure; may explode if heated.  
 Causes serious eye irritation.

**Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
 Do not spray on an open flame or other ignition source.  
 Do not pierce or burn, even after use.  
 Wash hands thoroughly after handling.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 If eye irritation persists: Get medical advice/attention.  
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
 Protect from sunlight. Store in a well-ventilated place.

**3 Composition/information on ingredients****Chemical characterization: Mixtures****Chemical Description:**

This product is a mixture of the substances listed below with nonhazardous additions.

**Dangerous components:**

|            |                   |        |
|------------|-------------------|--------|
| 64742-89-8 | VM&P Naphtha      | 19.47% |
| 74-98-6    | propane           | 17.64% |
| 106-97-8   | n-butane          | 10.36% |
| 1317-65-3  | Calcium Carbonate | 8.45%  |
| 64742-47-8 | Mineral Spirits   | 4.57%  |
| 13463-67-7 | titanium dioxide  | 2.86%  |

**4 First-aid measures**

**After inhalation:** Supply fresh air; consult doctor in case of complaints.  
**After skin contact:** Remove contaminated clothing. Wash exposed area with soap and water.  
**After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.  
**After swallowing:** Rinse mouth with water. Do not induce vomiting.  
**Most important symptoms and effects:** Dizziness  
**Indication of any immediate medical attention needed:** No further relevant information available.

**5 Fire-fighting measures**

**Extinguishing agents:** CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray.  
**Special hazards:** Can form explosive gas-air mixtures.  
**Protective equipment for firefighters:** A respiratory protective device may be necessary.

**6 Accidental release measures**

**Personal precautions, protective equipment and emergency procedures:** Use respiratory protective device against the effects of fumes/dust/aerosol.  
**Methods and material for containment and cleaning up:** Absorb liquid components with liquid-binding material.

**7 Handling and storage**

**Precautions for safe handling:** Use only in well ventilated areas.  
**Storage requirements:** Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

(Contd. on page 2)

## Safety Data Sheet

Printing date 11/23/2015

Revised On 11/23/2015

Trade name: 1436 COVER UP

(Contd. of page 1)

**8 Exposure controls/personal protection****Components with limit values that require monitoring at the workplace:****74-98-6 propane**

|           |  |
|-----------|--|
| PEL (USA) | Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm |
| REL (USA) | Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm |
| TLV (USA) | refer to Appendix F in TLVs and BEIs book          |

**106-97-8 n-butane**

|           |   |
|-----------|---|
| REL (USA) | Long-term value: 1900 mg/m <sup>3</sup> , 800 ppm   |
| TLV (USA) | Short-term value: 2370 mg/m <sup>3</sup> , 1000 ppm |

|                             |   |
|-----------------------------|---|
| <b>Hygienic protection:</b> | Wash hands after use.<br>Do not eat or drink while working.   |
| <b>Breathing equipment:</b> | A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene. |
| <b>Hand protection:</b>     | Protective gloves. The glove material must be impermeable and resistant to the substance.   |
| <b>Eye protection:</b>      | Tightly sealed goggles  |

**9 Physical and chemical properties**

|  |  |
|--|--|
| <b>Appearance:</b>                             | Aerosol.   |
| <b>Odor:</b>                                   | Aromatic   |
| <b>Odor threshold:</b>                         | Not determined.  |
| <b>pH-value:</b>                               | Not determined.  |
| <b>Melting point/Melting range</b>             | Undetermined.  |
| <b>Boiling point:</b>                          | -44 °C (-47 °F)  |
| <b>Flash point:</b>                            | -19 °C (-2 °F)   |
| <b>Flammability (solid, gas):</b>              | Extremely flammable.                                     |
| <b>Decomposition temperature:</b>              | Not determined.  |
| <b>Auto igniting:</b>                          | Product is not self-igniting.                            |
| <b>Danger of explosion:</b>                    | In use, may form flammable/explosive vapour-air mixture. |
| <b>Lower Explosion Limit:</b>                  | 1.5 Vol %  |
| <b>Upper Explosion Limit:</b>                  | 10.9 Vol %   |
| <b>Vapor pressure:</b>                         | Not determined.  |
| <b>Relative Density:</b>                       | Between 0.77 and 0.85 (Water equals 1.00)                |
| <b>Vapour density</b>                          | Not determined.  |
| <b>Evaporation rate</b>                        | Not applicable.  |
| <b>Partition coefficient: n-octonal/water:</b> | Not determined.  |
| <b>Solubility:</b>                             | Not determined.  |
| <b>Viscosity:</b>                              | Not determined.  |
| <b>VOC content:</b>                            | 492.6 g/l / 4.11 lb/gl                                   |
| <b>VOC content (less exempt solvents):</b>     | 53.6 %   |
| <b>Water:</b>                                  | 19.7 %   |
| <b>MIR Value:</b>                              | 0.60   |
| <b>Solids content:</b>                         | 72.0 %   |

**10 Stability and reactivity**

|  |  |
|--|--|
| <b>Reactivity:</b>                         | Stable at normal temperatures.   |
| <b>Conditions to avoid:</b>                | Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures. |
| <b>Chemical stability:</b>                 | Not fully evaluated.   |
| <b>Possibility of hazardous reactions:</b> | No dangerous reactions known.  |
| <b>Incompatible materials:</b>             | No further relevant information available.   |
| <b>Hazardous decomposition:</b>            | No dangerous decomposition products known.   |

**11 Toxicological information****LD/LC50 values that are relevant for classification:****106-97-8 n-butane**

Inhalative LC50/4 h 658 mg/l (rat)

**13463-67-7 titanium dioxide**

|            |          |                    |
|------------|----------|--------------------|
| Oral       | LD50     | >20000 mg/kg (rat) |
| Dermal     | LD50     | >10000 mg/kg (rbt) |
| Inhalative | LC50/4 h | >6.82 mg/l (rat)   |

|  |                               |
|--|-------------------------------|
| <b>Information on toxicological effects:</b> | No data available.            |
| <b>Skin effects:</b>                         | No irritant effect.           |
| <b>Eye effects:</b>                          | No irritating effect.         |
| <b>Sensitization:</b>                        | No sensitizing effects known. |

(Contd. on page 3)

## Safety Data Sheet

Printing date 11/23/2015

Revised On 11/23/2015

Trade name: 1436 COVER UP

(Contd. of page 2)

**Carcinogenic categories****IARC (International Agency for Research on Cancer)**

|            |                      |    |
|------------|----------------------|----|
| 1317-60-8  | Micaceous Iron Oxide | 3  |
| 13463-67-7 | titanium dioxide     | 2B |

**NTP (National Toxicology Program)**

None of the ingredients is listed.

**12 Ecological information**

|                                       |   |
|---------------------------------------|---|
| <b>Aquatic toxicity:</b>              | Hazardous for water, do not empty into drains.                                      |
| <b>Persistence and degradability:</b> | The product is degradable after prolonged exposure to natural weathering processes. |
| <b>Bioaccumulative potential:</b>     | No further relevant information available.  |
| <b>Mobility in soil:</b>              | No further relevant information available.  |
| <b>Other adverse effects:</b>         | No further relevant information available.  |

**13 Disposal considerations**

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

**Recommendation:** Completely empty cans should be recycled.

**14 Transport information**

|                                      |   |
|--------------------------------------|---|
| <b>UN-Number</b>                     | UN1950  |
| <b>DOT</b>                           | N/A   |
| <b>DOT</b>                           | Consumer Commodity ORM-D<br>Aerosols, flammable                     |
| <b>ADR</b>                           | 1950 Aerosols   |
| <b>Transport hazard class(es):</b>   |   |
| <b>Class</b>                         | 2.1   |
| <b>Marine pollutant:</b>             | No  |
| <b>Special precautions for user:</b> | Warning: Gases  |
| <b>EMS Number:</b>                   | F-D,S-U   |
| <b>Quantity limitations</b>          | On passenger aircraft/rail: 75 kg<br>On cargo aircraft only: 150 kg |

|                                 |  |
|---------------------------------|--|
| <b>ADR</b>                      |  |
| <b>Excepted quantities (EQ)</b> | Code: E0<br>Not permitted as Excepted Quantity |

**IMDG**

|                                 |  |
|---------------------------------|--|
| <b>Limited quantities (LQ)</b>  | 1L   |
| <b>Excepted quantities (EQ)</b> | Code: E0<br>Not permitted as Excepted Quantity |
| <b>Packaging Group:</b>         | --   |
| <b>UN "Model Regulation":</b>   | UN1950, Aerosols, 2.1                          |

**15 Regulatory information****SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

**SARA Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

**CPSC:** This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

**California Proposition 65 chemicals known to cause cancer:**

|            |                  |
|------------|------------------|
| 13463-67-7 | titanium dioxide |
| 100-41-4   | ethyl benzene    |
| 1333-86-4  | Carbon black     |

**CANADIAN ENVIRONMENTAL PROTECTION ACT:**

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

**EPA:**

None of the ingredients is listed.

**16 Other information**

|  |                    |
|--|--------------------|
| <b>Contact:</b>                            | Regulatory Affairs |
| <b>Date of preparation / last revision</b> | 11/23/2015 / -     |