

# Safety Data Sheet Champion Chemical Co.

24 Hour Emergency Phone Numbers:

Transportation/Spill/Leak:

Medical Emergency/Information: 800-451-8346 (24 hrs)

CHEMTREC 800-424-9300

Revision Date: 03-Jan-2015

1. PRODUCT AND COMPANY IDENTIFICATION

**Product Identifier** 

Product Name: Super-Strip

Product Number: 270

Recommended Use: Floor Finish Remover

Uses Advised Against: For Industrial and Institutional Use Only

Manufacturer/Supplier: Champion Chemical Co.

8319 S. Greenleaf Ave. Whittier, CA 90602 800-621-7868

www.championchemical.com

### 2. HAZARDS IDENTIFICATION

**GHS Classification** 

Acute toxicity - Inhalation (Vapors)
Skin Corrosion/Irritation:
Category 1
Serious Eye Damage/Eye Irritation:
Category 1

**GHS Label Elements** 

Signal Word:

Symbols:

Hazard Statements: Harmful if inhaled.

Causes severe skin burns and serious eye damage.

Precautionary Statements:

**Prevention:** Use only outdoors or in a well-ventilated area.

Danger

Do not breathe mist, vapors or spray.

Wash hands and any exposed skin thoroughly after handling.

Wear protective gloves. Wear eye / face protection. Wear protective clothing.

Response: IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

**-Eyes** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

**-Skin** IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

or shower. Wash contaminated clothing before reuse.

**-Inhalation:** IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

-Ingestion: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

-Specific Treatment: See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.

Storage: Store locked up.

**Disposal:** Dispose of contents and container in accordance with local, state and federal regulations.

Hazards Not Otherwise Classified: Not Applicable

Other Information:

• Harmful if swallowed

Harmful contact may not cause immediate pain.

· Harmful if absorbed through skin.

Inhalation of vapors or mist may cause respiratory irritation or damage.

· Keep out of reach of children.

Revision Date: 3-Jan-2015 270 - Super-Strip

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Potassium Hydroxide	1310-58-3	7-8
2-butoxyethanol	111-76-2	9-12
Benzene Sulfonic Acid Derivative	701-75-1	1-5
Anionic Surfactant	Trade Secret	1-2
Sodium Metasilicate	6834-92-0	2-4

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

-Skin Contact:

-Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and

> easy to do. Continue rinsing. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Take off immediately all contaminated clothing and shoes. Rinse with water or shower for

at least 15 minutes. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Wash

contaminated clothing before reuse. Discard or destroy contaminated shoes.

Remove victim to fresh air and keep at rest in a position comfortable for breathing. -Inhalation:

IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Call a poison control center or

physician if you feel unwell.

Rinse mouth. Do NOT induce vomiting. IMMEDIATELY CALL A POISON CENTER OR -Ingestion:

PHYSICIAN. Never give anything by mouth to an unconscious person.

Treat symptomatically. Note to Physicians:

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:

Specific Hazards Arising from the

Chemical:

**Hazardous Combustion Products:** 

Use Dry chemical Carbon dioxide Water spray (fog) Alcohol resistant foam

Dried product is capable of burning. Combustion products are toxic.

May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.

**Protective Equipment and Precautions for Firefighters:**  Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full

protective gear. Cool fire-exposed containers with water spray.

6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** 

**Environmental Precautions:** Methods for Clean-Up:

Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

Do not rinse spill onto the ground, into storm sewers or bodies of water.

Prevent further leakage or spillage if safe to do so. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

7. HANDLING AND STORAGE

Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly Advice on Safe Handling:

after handling. Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach **Storage Conditions:** 

of children. Keep from freezing.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Occupational Exposure Limits:** 

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH
2-butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m <sup>3</sup>	IDLH: 700 ppm TWA: 5 ppm
111-70-2		(vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m³	TWA: 24 mg/m <sup>3</sup>
		(vacated) TVVA: 120 mg/m (vacated) S*	

**Engineering Controls:** Provide good general ventilation.

If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other engineering controls should be

considered

Eye wash stations and shower facilities should be readily accessible in

**Personal Protective Equipment** 

areas where the product is handled.

**Eye/Face Protection: Skin and Body Protection:**  Wear splash goggles. For severe use-conditions, wear a face shield over the goggles. Wear rubber or other chemical-resistant gloves and solvent / alkali resistant boots. The use of other protective equipment should be considered in order to prevent or minimize contact with this product.

Not required with expected use. **Respiratory Protection:** 

If occupational exposure limits are exceeded or respiratory irritation occurs, use of a NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section 3 should be considered.

**General Hygiene Considerations:** Wash hands and any exposed skin thoroughly after handling.

See 29 CFR 1910.132-138 for further guidance.

270 - Super-Strip Revision Date: 3-Jan-2015

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical State:	rance/Physical State: Liquid		
Color:	Yellow		
Odor:	Mild Scent		
pH:	12-14		
Melting Point / Freezing Point:	No information available.		
Boiling Point / Boiling Range:	94 °C / 201 °F		
Flash Point:	> 200 °F		
Evaporation Rate:	< 1 (Butyl acetate = 1)		
Flammability (solid, gas)	No information available.		
Upper Flammability Limit:	No information available.		
Lower Flammability Limit:	No information available.		
Vapor Pressure:	No information available.		
Vapor Density:	No information available.		
Specific Gravity:	1.05		
Solubility(ies):	Soluble in water		
Partition Coefficient:	No information available.		
Autoignition Temperature:	No information available.		
Decomposition Temperature:	No information available.		
Viscosity:	No information available.		

# 10. STABILITY AND REACTIVITY

**Reactivity:** This material is considered to be non-reactive under normal conditions of use.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Not expected to occur with normal handling and storage.

Conditions to Avoid: Extremes of temperature and direct sunlight. Incompatible Materials: Strong oxidizing agents. Strong acids.

Hazardous Decomposition May include carbon monoxide, carbon dioxide (CO2) and other toxic gases or vapors.

**Products:** 

# 11. TOXICOLOGICAL INFORMATION

**Likely Routes of Exposure:** Eyes, Skin, Ingestion, Inhalation.

Symptoms of Exposure:

**-Eye Contact:** Pain, redness, swelling of the conjunctiva and tissue damage. Eye contact may cause

permanent damage.

**-Skin Contact:** Pain, redness, blistering and possible chemical burn.

**-Inhalation:** Irritation or damage to the mucus membranes of the respiratory tract. Inhalation of vapors in

high concentration may cause irritation of respiratory system

**-Ingestion:** Damage or chemical burns to mouth, throat and stomach. Pain, nausea, vomiting and

diarrhea.

Immediate, Delayed, Chronic Effects

Product Information: Data not available or insufficient for classification.

Chronic Toxicity: May cause adverse effects on the bone marrow and blood-forming system. May cause

adverse liver effects.

Target Organ Effects: Blood. Central nervous system. -Eyes. hematopoietic system. kidney. Liver. Respiratory

System. -Skin.

**Numerical Measures of Toxicity** 

The following acute toxicity estimates (ATE) are calculated based on the GHS document.

ATEmix (oral): 2807 mg/kg
ATEmix (dermal): 5462 mg/kg
ATEmix (inhalation-dust/mist): 10.1 mg/l
ATEmix (inhalation-vapor): 14.5 mg/l

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50	
Sodium Metasilicate 6834-92-0	1,152 - 1,349 mg/kg (Rat)	no data available	no data available	
Potassium Hydroxide 1310-58-3	333 mg/kg(Rat )	no data available	no data available	

Carcinogenicity: No components present at 0.1% or greater are listed as to being carcinogens by ACGIH, IARC, NTP or OSHA.

270 - Super-Strip Revision Date: 3-Jan-2015

### 12. ECOLOGICAL INFORMATION

**Ecotoxicity** 

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
2-butoxyethanol 111-76-2	Not Available	1490: 96 h Lepomis macrochirus mg/L LC50 static 2950: 96 h Lepomis macrochirus mg/L LC50	Not Available	1698 - 1940: 24 h Daphnia magna mg/L EC50 1000: 48 h Daphnia magna mg/L EC50
Sodium Metasilicate 6834-92-0	no data available	semi-static test LC50 Danio rerio (zebra fish) 210 mg/l - 96 h	no data available	no data available
Potassium Hydroxide 1310-58-3	no data available	LC50 - Gambusia affinis (Mosquito fish) - 80 mg/l - 96 h	no data available	no data available

Persistence and Degradability:No information available.Bioaccumulation:No information available.

Other Adverse Effects: No information available.

# 13. DISPOSAL CONSIDERATIONS

**Disposal of Wastes:**Contaminated Packaging:
Dispose of in accordance with federal, state and local regulations.
Dispose of in accordance with federal, state and local regulations.

### 14. TRANSPORT INFORMATION

**DOT:** Not Regulated

Proper Shipping Name: Non-Hazardous Product

# 15. REGULATORY INFORMATION

**TSCA Status:** (Toxic Substance Control Act Section 8(b) Inventory)

All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

### **SARA 313**

This product contains the following listed substances:

# 2-butoxyethanol

CAS No 111-76-2 applies to R-(OCH2CH2)n-OR', where n = 1, 2, or 3, R=Alkyl C7 or less, or R = Phenyl or Alkyl substituted phenyl, R' = H or Alkyl C7 or less, or OR' consisting of Carboxylic acid ester, Sulfate, Phosphate, Nitrate, or Sulfonate, Chemical Category N230

# SARA 311/312 Hazard Categories

Acute Health Hazard: Yes
Chronic Health Hazard: No
Fire Hazard: Yes
Sudden release of pressure hazard: No
Reactive Hazard: No

### **California Proposition 65**

This product does not contains Proposition 65 chemicals

### 16. OTHER INFORMATION

NFPA Health Hazards: 3 Flammability: 0 Instability: 0 Special: N/A

Health Hazards: 3 Flammability: 0 Physical Hazards: 0

Revision Date: 3-JAN-2015

Reasons for Revision: No information available.

# Disclaimer:

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**