SAFETY DATA SHEET



Date of issue/Date of revision6 December 2016Version 4.01

Section 1. Identification				
Product name	: 76-110 SUN PROOF HOUSE/TRIM PAINT EXTERIOR SATIN-WHITE/PASTEL BASE			
Product code	: 00410952			
Other means of identification	: Not available.			
Product type	: Liquid.			
Relevant identified uses of	the substance or mixture and uses advised against			
Product use	: Industrial applications, Used by spraying.			
Use of the substance/ mixture	: Coating.			
Uses advised against	: Not applicable.			
Manufacturer	: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272			
Emergency telephone number	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) 01-800-00-21-400 (Mexico)			
Technical Phone Number	: 1-800-441-9695 (8:00 am to 5:00 pm EST)			

Section 2. Hazards identification

OSHA/HCS status	 This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	 SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (kidneys) - Category 2
	Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 23.3%
<u>GHS label elements</u> Hazard pictograms	

Signal word

: Warning

Product name 76-110 SUN PROOF HOUSE/TRIM PAINT EXTERIOR SATIN-WHITE/PASTEL BASE

Section 2. Hazards identification

Hazard statements	 May cause an allergic skin reaction. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. (kidneys)
Precautionary statements	
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Do not breathe vapor. Contaminated work clothing must not be allowed out of the workplace.
Response	: Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Avoid contact with skin and clothing. Wash thoroughly after handling. Emits toxic fumes when heated.
Hazards not otherwise classified	: Prolonged or repeated contact may dry skin and cause irritation.

Section 3. Composition/information on ingredients

Substance/mixture

- : Mixture
- Product name
- : 76-110 SUN PROOF HOUSE/TRIM PAINT EXTERIOR SATIN-WHITE/PASTEL BASE

Ingredient name	%	CAS number
titanium dioxide	≥10 - ≤20	13463-67-7
ethanediol	≥1.0 - ≤5.0	107-21-1
Diatomaceous earth	≥1.0 - ≤5.0	61790-53-2
Petroleum Derivatives	≥1.0 - ≤5.0	Not available.
octhilinone (ISO)	<1.0	26530-20-1

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person. Description of necessary first aid measures

Eye contact

: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

Product name 76-110 SUN PROOF HOUSE/TRIM PAINT EXTERIOR SATIN-WHITE/PASTEL BASE

Section 4. First aid measures

Inhalation	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.				
Skin contact	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.				
Ingestion	If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.				
Most important symptoms/	effects, acute and delayed				
Potential acute health effe	<u>cts</u>				
Eye contact	: No known significant effects or critical hazards.				
Inhalation	: No known significant effects or critical hazards.				
Skin contact	: Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.				
Ingestion	: No known significant effects or critical hazards.				
Over-exposure signs/sym	<u>otoms</u>				
Eye contact	: No specific data.				
Inhalation	: No specific data.				
Skin contact	: Adverse symptoms may include the following: irritation redness dryness cracking				
Ingestion	: No specific data.				
Indication of immediate me	dical attention and special treatment needed, if necessary				
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. 				
Specific treatments	: No specific treatment.				
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.				

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media		
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.	
Unsuitable extinguishing media	: None known.	

Product name 76-110 SUN PROOF HOUSE/TRIM PAINT EXTERIOR SATIN-WHITE/PASTEL BASE

Section 5. Fire-fighting measures

_	·
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides metal oxide/oxides
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protec	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ont	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Product name 76-110 SUN PROOF HOUSE/TRIM PAINT EXTERIOR SATIN-WHITE/PASTEL BASE

Section 7. Handling and storage

Precautions for safe handling

Protective measures	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Special precautions	If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

= Fume

F

Occupational exposure limits

Ingredient name	Exposure limits				
titanium dioxide	OSHA PEL (United States, 2/2013).				
	TWA: 15 mg/m ³ 8 hours. Form: Total dust				
	ACGIH TLV (United States, 3/2015).				
	TWA: 10 mg/m ³ 8 hours.				
ethanediol	ACGIH TLV (United States, 3/2015).				
	C: 100 mg/m ³ Form: Aerosol				
Diatomaceous earth	OSHA PEL Z3 (United States, 2/2013).				
	TWA: 20 mppcf 8 hours.				
	TWA: 80 mg/m ³ / (%SiO2) 8 hours.				
Petroleum Derivatives	OSHA PEL (United States).				
	TWA: 5 mg/m³				
	STEL: 10 mg/m ³				
octhilinone (ISO)	None.				
Key to abbreviatio	ns				
A = Acceptable Maximum Peak	S = Potential skin absorption				
ACGIH = American Conference of Governmental Industrial Hygienists.	SR = Respiratory sensitization				
C = Ceiling Limit	SS = Skin sensitization				

STEL = Short term Exposure limit values

United States Page: 5/12

Product name 76-110 SUN PROOF HOUSE/TRIM PAINT EXTERIOR SATIN-WHITE/PASTEL BASE

Section 8. Exposure controls/personal protection

		•	•		
IPEL	 Internal Permissible Exposure Limit 			TD	= Total dust
OSHA	= Occupational Safety and Health Administration	on.		TLV	= Threshold Limit Value
R	= Respirable			TWA	= Time Weighted Average
7	= OSHA 29 CER 1910 1200 Subpart 7 - Toxic a	and Hazardous Su	bstances		

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures	:	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	:	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measure	<u>S</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection Skin protection	: Safety glasses with side shields.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	: butyl rubber
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Product name 76-110 SUN PROOF HOUSE/TRIM PAINT EXTERIOR SATIN-WHITE/PASTEL BASE

Section 9. Physical and chemical properties

Appearance

<u>Appoulation</u>	
Physical state	: Liquid.
Color	: Not available.
Odor	: Characteristic.
Odor threshold	: Not available.
рН	: Not available.
Melting point	: Not available.
Boiling point	: >37.78°C (>100°F)
Flash point	: Closed cup: 113.33°C (236°F) [Product does not sustain combustion.]
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Upper: 0%
Evaporation rate	: Not available.
Vapor pressure	: Not available.
Vapor density	: Not available.
Relative density	: 1.15
Density(lbs / gal)	: 9.6
Solubility	: Soluble in the following materials: cold water.
Partition coefficient: n- octanol/water	: Not available.
Viscosity	: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)
Volatility	: 70% (v/v), 62.208% (w/w)
% Solid. (w/w)	: 37.792

Section 10. Stability and reactivity

	United States Page: 7/12
Hazardous decomposition products	: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Chemical stability	: The product is stable.
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.

Product name 76-110 SUN PROOF HOUSE/TRIM PAINT EXTERIOR SATIN-WHITE/PASTEL BASE

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

<u>Addic toxicity</u>						
Product/ingredient name	Result			Species	Dose	Exposure
titanium dioxide	LD50 Oral			Rat	>11 g/kg	-
ethanediol	LD50 Derr			Rabbit	9.53 g/kg	-
(120)	LD50 Oral			Rat	4700 mg/kg	-
octhilinone (ISO)	LD50 Derr LD50 Oral			Rabbit Rat	0.69 g/kg 0.55 g/kg	-
Conclusion/Summary Irritation/Corrosion Conclusion/Summary			available on th	e mixture itse		L
Skin	: There are	e no data a	available on th	e mixture itse	lf.	
Eyes	: There are	e no data a	available on th	e mixture itse	lf.	
Respiratory	: There are	e no data a	available on th	e mixture itse	lf.	
<u>Sensitization</u>						
Conclusion/Summary						
Skin	: There are	e no data a	available on th	e mixture itse	lf.	
Respiratory	: There are	e no data a	available on th	e mixture itse	lf.	
<u>Mutagenicity</u>						
Conclusion/Summary	: There are	e no data a	available on th	e mixture itse	lf.	
Carcinogenicity						
Conclusion/Summary	: There are	e no data a	available on th	e mixture itse	lf.	
Classification						
Product/ingredient name	OSHA	IARC	NTP			
titanium dioxide	-	2B	-			
Diatomaceous earth	-	3	-			
Carcinogen Classification	code:	1	1			
IARC: 1, 2A, 2B, 3, NTP: Known to be OSHA: + Not listed/not regu	4 e a human caro	cinogen; Rea	isonably anticip	ated to be a hum	an carcinogen	
Reproductive toxicity						
Conclusion/Summary	: There are	e no data a	vailable on the	e mixture itsel	f.	
<u>Feratogenicity</u>						
Conclusion/Summary	: There are	e no data a	vailable on the	e mixture itsel	f.	
Specific target organ toxicity	<u>(single exr</u>	<u>oosure)</u>				
Name						Category
Petroleum Derivatives						Category 3

Specific target organ toxicity (repeated exposure)

United States	Page: 8/12
---------------	------------

Product name 76-110 SUN PROOF HOUSE/TRIM PAINT EXTERIOR SATIN-WHITE/PASTEL BASE

Section 11. Toxicological information

Name		Category
ethanediol		Category 2
Target organs	: Contains material which may cause damage to the follo tract, skin, central nervous system (CNS), eye, lens or	
Aspiration hazard Not available.		
nformation on the likely ro	utes of exposure	
Potential acute health effe	ects	
Eye contact	: No known significant effects or critical hazards.	
Inhalation	: No known significant effects or critical hazards.	
Skin contact	: Defatting to the skin. May cause skin dryness and irrita reaction.	ation. May cause an allergic ski
Ingestion	: No known significant effects or critical hazards.	
Over-exposure signs/sym	<u>ptoms</u>	
Eye contact	: No specific data.	
Inhalation	: No specific data.	
Skin contact	: Adverse symptoms may include the following: irritation redness dryness cracking	
Ingestion	: No specific data.	
Delayed and immediate effe	ects and also chronic effects from short and long term e	<u>xposure</u>
Conclusion/Summary	: There are no data available on the mixture itself. If splacause irritation and reversible damage. Ingestion may vomiting. This takes into account, where known, delay also chronic effects of components from short-term and inhalation and dermal routes of exposure and eye contained.	cause nausea, diarrhea and red and immediate effects and d long-term exposure by oral,
Short term exposure		
Potential immediate effects	: There are no data available on the mixture itself.	
Potential delayed effects	: There are no data available on the mixture itself.	
Long term exposure Potential immediate effects	: There are no data available on the mixture itself.	
Potential delayed effects	: There are no data available on the mixture itself.	
i otential delayed effects		
Potential chronic health eff		
Potential chronic health ef General	: May cause damage to organs through prolonged or represented contact can defat the skin and lead to irritation Once sensitized, a severe allergic reaction may occur ward low levels	n, cracking and/or dermatitis.
	repeated contact can defat the skin and lead to irritation	n, cracking and/or dermatitis. when subsequently exposed to

United States Page: 9/12

Date of issue 6 December 2016 Version 4.01

Product name 76-110 SUN PROOF HOUSE/TRIM PAINT EXTERIOR SATIN-WHITE/PASTEL BASE

Section 11. Toxicological information

- **Teratogenicity** : No known significant effects or critical hazards.
- **Developmental effects** : No known significant effects or critical hazards.
 - : No known significant effects or critical hazards.

Numerical measures of toxicity Acute toxicity estimates

Fertility effects

Route	ATE value
Oral	17374.7 mg/kg

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute LC50 >100 mg/l Fresh water	Daphnia - Daphnia magna	48 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
ethanediol	-1.36	-	low
octhilinone (ISO)	2.45	-	low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Section 13. Disposal considerations

th W wl sa cle	gional local authority requirements. Dispose of surplus and non-recyclable products a a licensed waste disposal contractor. Waste should not be disposed of untreated to e sewer unless fully compliant with the requirements of all authorities with jurisdiction. 'aste packaging should be recycled. Incineration or landfill should only be considered nen recycling is not feasible. This material and its container must be disposed of in a afe way. Care should be taken when handling emptied containers that have not been eaned or rinsed out. Empty containers or liners may retain some product residues. void dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
	void dispersal of spilled material and runoff and contact with soil, waterways, drains

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

Product name 76-110 SUN PROOF HOUSE/TRIM PAINT EXTERIOR SATIN-WHITE/PASTEL BASE

14. Transport information

	DOT	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

DOT	: None identified.
IMDG	: None identified.
ΙΑΤΑ	: None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

United States

United States inventory (TSCA 8b) : All components are listed or exempted.

SARA 302/304

SARA 304 RQ : Not applicable.

Composition/information on ingredients

No products were found.

SARA 311/312

Classification

: Immediate (acute) health hazard Delayed (chronic) health hazard

Composition/information on ingredients

Name	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
titanium dioxide	No.	No.	No.	No.	Yes.
ethanediol	No.	No.	No.	Yes.	Yes.
Diatomaceous earth	Yes.	No.	No.	No.	No.
Petroleum Derivatives	No.	No.	No.	Yes.	No.
octhilinone (ISO)	No.	No.	No.	Yes.	No.

United States Page: 11/12

Product name 76-110 SUN PROOF HOUSE/TRIM PAINT EXTERIOR SATIN-WHITE/PASTEL BASE

Section 15. Regulatory information

<u>SARA 313</u>

Supplier notification

Chemical name

: ethanediol

CAS number 107-21-1 Concentration 1 - 5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health : 2 * Flammability : 1 Physical hazards : 0 (*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Ass	ociation (U.S.A.)		
Health : 2 Flamma	ibility : 1 Instability : 0		
Date of previous issue	: 9/3/2016		
Organization that prepared the MSDS	: EHS		
Key to abbreviations	 ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations 		

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.